

POWER[®] *seal* S 60V



Rozsah použití

Teplota: -60 °C ~ +230 °C

Tlak: 20 bar

Rychlost: 25 m/sec

Materiálové složení

Kovové části: SS 316 L / Hastelloy C / Inconel - 718

Rotační plochy: CA / SC / SiC / TC

O-kroužky: EPDM / Viton / FEP / Kalrez

mm

Ø hřídele D	D1	L
25	37.0	31.8
28	42.8	31.8
30	43.0	33.3
32	43.0	33.3
33	49.2	36.5
35	49.2	36.5
38	49.4	36.5
40	55.5	36.5
43	58.7	36.5
45	58.7	36.5
48	61.9	38.1
50	65.1	38.1
53	68.2	38.1
55	71.4	39.7
60	74.6	39.7
63	80.9	39.7
65	84.1	41.3
70	87.3	41.3
75	95.2	42.8
80	98.4	44.5
82	104.8	44.5
90	108.0	47.6
95	114.3	47.6
100	120.7	47.6
110	130.0	47.6

inch

Ø hřídele D	D1	L
.750	1.475	1.250
.875	1.475	1.250
1.000	1.475	1.250
1.125	1.687	1.250
1.250	1.812	1.312
1.250	1.694	1.312
1.375	1.937	1.437
1.500	2.062	1.437
1.500	1.944	1.437
1.625	2.187	1.437
1.750	2.312	1.437
1.875	2.437	1.500
2.000	2.562	1.500
2.125	2.687	1.500
2.250	2.812	1.562
2.375	2.937	1.562
2.500	3.187	1.562
2.625	3.312	1.625
2.750	3.437	1.625
2.875	3.625	1.687
3.000	3.750	1.687
3.125	3.875	1.750
3.250	4.000	1.750
3.375	4.125	1.750
3.500	4.250	1.875
3.625	4.375	1.875
3.750	4.500	1.875
3.875	4.625	1.875
4.000	4.750	1.875
4.125	5.125	1.875
4.250	5.125	1.875
4.375	5.375	1.875
4.500	5.375	1.875
4.625	5.625	1.875
4.750	5.625	1.875